

**Ram
mer®**

**Ram
mer®**

EN

LARGE RANGE HAMMERS

EVERY HIT COUNTS

The world's best-known and most-respected brand of hydraulic hammers, Rammer offers a comprehensive range of powerful, productive and durable attachments that are suitable for carriers in the 0.6 to 100 tons operating weight class.

The Rammer Large range is unsurpassed in its innovation and reliability and offers class-leading power-to-weight characteristics that mark them as the best in their class.

Rammer's product selection is supported by a dedicated global dealer network with ready access to Genuine Rammer parts and a wealth of operational knowledge and experience to ensure that your Rammer hammer continues to contribute to your company's profitability for its entire working life.

SANDVIK IS THE WORLD'S LEADING MANUFACTURER OF HYDRAULIC HAMMERS AND ATTACHMENTS. OVER THE PAST 35 YEARS, SANDVIK-OWNED RAMMER HAMMERS HAVE BEEN DEVELOPED IN CONJUNCTION WITH OUR CUSTOMERS ACROSS THE WORLD. AS A RESULT, THEY ARE TOUGH, DURABLE, RELIABLE AND OFFER THE MOST ECONOMICAL OWNING AND OPERATING COSTS WHILE DELIVERING MAXIMUM PRODUCTION.



Rammer®

ISO 9001

ISO 18001

ISO 14001

ALL RAMMER HAMMERS COME FULLY CE COMPLIANT, SUPPLIED BY SANDVIK, LAHTI, FINLAND. THEY ARE MANUFACTURED IN ACCORDANCE WITH ISO STANDARDS.

SAFETY IS A TOP PRIORITY IN EVERYTHING WE DO

In the factory

Safety is the primary consideration. Visitors are to consider and improve safety to help us achieve our aim of zero accidents.

Products

Safety is the driving force behind the development of all our products. Our aim is to set the safety standard by making products that are safe to operate and maintain. Rammer operator and service training packages reinforce that message to ensure the safety of your entire workforce.

Process

Rammer products also improve the safety of the working site and its processes. For example when breaking oversize material, it reduces loading and hauling and prevents blockages and bridging during the crushing process.

Safety – Your Advantage

Injuries can impact upon an entire workforce and resulting in lost working days and a loss of production. A safe site is a productive site.

Environment

Rammer products are manufactured utilizing state-of-the-art, ISO standards technology that consumes the minimum electricity, and recycles cutting fluids and metal chips. Furthermore, when Rammer breakers reach the end of their useful working life, more than 90 percent of the metallic components can be recycled.





OUR FEATURES – YOUR BENEFITS

INCREASE YOUR PRODUCTIVITY

1 FBE (Fixed Blow Energy)

A built-in pressure control valve maintains hydraulic pressure levels to ensure that every blow delivers the maximum power possible for optimum productivity.

2 Membrane type accumulator

Membrane type accumulator eliminates nitrogen leakages, ensuring maximum piston acceleration and removing the need for time consuming recharging.

3 Stroke selector

Fitted as standard on all Large range hammers (except 7013) Stroke selector is designed to optimize hammer operating. It allows operator to match hammer to material and application, delivering more frequent, softer blows in softer materials and fewer high impact blows in hard rock.

4 IBP (Idle Blow Protection)

Fitted as standard on all Large range hammers (except 7013), IBP ensures the hammer cannot be operated until pressure is placed on tool. This eliminates tie rod stress, reduces oil overheating and protects against premature failures.

5 Wide tool selection

PROTECT YOUR WORKING ENVIRONMENT

6 Heavy duty housing

Fitted as standard, heavy duty housings feature a robust structure, minimum number of holes and plastic wear plates for optimum hammer protection and noise reduction.

7 Top buffer and side pads

The unique Rammer vibration absorption system consists of three buffers - one upper buffer and two side pads – that prevent the transmission of vibration to protect both the breaker and the carrier's boom, stick and swing gears and to isolate the operator.

MINIMIZE YOUR MAINTENANCE COSTS

8 Ramdata II

The Ramdata II service indicator is designed to help hammer operators and service personnel get information about the service interval status, service history and accumulated working history of the hammer.

9 Ramlube (Different options)

Rammer offers two types of automatic greasing systems for its Large Hammer Range:

Ramlube I - Machine-mounted
Ramlube II - Hammer-mounted

Both Ramlube devices maintain correct greasing levels, protect the tool and reduce owning and operating costs.

2 Membrane type accumulator

Membrane type accumulator eliminates nitrogen leakages, ensuring maximum piston acceleration and removing the need for time consuming recharging.

12 TS (Tool Saver) bushing

Rammer Large range hammers can be equipped as a retrofit with a field replaceable insert that increases service life of the tool and tool bushing.

MAXIMIZE YOUR UTILIZATION

6 Heavy duty housing

Fitted as standard, heavy duty housings feature a robust structure, minimum number of holes and plastic wear plates for optimum hammer protection and noise reduction.

10 VIDAT

Vibration Dampened Tie Rods, spherical tie rod nuts and damper bushings ensure piston moves freely for longer, more productive working life.

11 Ramvalve

Ramvalve detects overflow, prevents damage from system overload and protects against premature failure. Ramvalve is standard on all Large range hammers (except 7013).

12 TS (Tool Saver) bushing

Rammer Large range hammers can be equipped as a retrofit with a field replaceable insert that increases service life of the tool and tool bushing.



FOR EVERY APPLICATION

	3288	4099	5011	7013
GENERAL CONSTRUCTION				
Breaking of road surface (concrete, asphalt)	C, P, LSC	C, P, LSC	C, P, LSC	C, P, LSC
Primary breaking to lay a road	C, LSC	C, LSC	C, LSC	C, LSC
Trenching	C, LSC	C, LSC	C, LSC	C, LSC
Rock excavation for base of housing	C, LSC	C, LSC	C, LSC	C, LSC
Breaking of frozen ground	C, M, P	C, M, P	C, M, P	C, M, P
DEMOLITION				
Demolition of concrete walls, roofs, floors	C, M, P	C, M, P	C, M, P	C, M, P
Breaking thick brick walls	C, M, P	C, M, P	-	-
Breaking heavily reinforced bridge pillars	B, C, P	B, C, P	B, C, P	B, C, P
Breaking massive reinforced concrete foundations	C, M, P	C, M, P	C, M, P	C, M, P
Rock trenches for mains or water supply	C, LSC	C, LSC	C, LSC	C, LSC
Separating rebar from concrete (for recycling)	B	B	B	B
QUARRYING				
Secondary breaking of blasted rock	B	B	B	B
Primary breaking of rock	C, LSC, HRC	C, LSC, HRC	C, LSC, HRC	C, LSC, HRC
Breaking oversizes on a crusher or feeder	B	B	-	-
MINING				
Primary tunneling	C, M, HRC	C, M, HRC	C, M, HRC	C, M, HRC
Trenching in tunnels	C, HRC	C, HRC	C, HRC	C, HRC
Blasting prohibited mining	C, M, LSC, HRC	C, M, LSC, HRC	C, M, LSC, HRC	C, M, LSC, HRC
Breaking of oversizes on grizzly or feed chute	B	B	-	-
Breaking of oversizes after blasting in the drift	B	B	B	B
METALLURGICAL				
Breaking of massive steel slag	-	B, C	B, C	B, C
Breaking of aluminium electrolyse slag	-	B, C	B, C	B, C
Breaking of ferrochrome blocks	B, C	B, C	B, C	B, C
UNDER WATER¹⁾				
Demolition under water	C, M, P	C, M, P	C, M, P	C, M, P
Rock breaking under water	C	C	C	C

¹⁾ Working under water needs special precautions, contact your local dealer for details.

RECOMMENDED HAMMER MODEL

Optimal Suitable

SYMBOL OF RECOMMENDED TOOLS

Chisel C Pyramid P
 Hard Rock Chisel HRC Blunt B
 Limestone Chisel LSC Super Blunt SB
 Moil point M Compacting plate CP

LARGE HAMMERS



3288

4099

Minimum working weight, kg (lb)	2400-2500 (5290-5510)	3380-3540 (7450-7800)
Impact rate, Long Stroke, bpm	370-630	400-560
Impact rate, Short Stroke, bpm	460-740	520-700
Operating pressure	150-160 (2175-2320)	150-160 (2175 - 2320)
Pressure relief, min bar (psi)	220 (3190)	210 (3045)
Pressure relief, max bar (psi)	240 (3480)	230 (3335)
Oil flow range, l/min (gal/min)	160-250 (42.3-66.0)	250-350 (66.0-92.5)
Back pressure, max bar (psi)	10 (145)	12 (175)
Input power, kW (hp)	67 (90)	93 (125)
Tool diameter, mm (in)	142 (5.59)	166 (6.54)
Carrier weight, allowed range, t (lb)	26-42 (57300-88200)	36-55 (75000-121300)
Noise level, measured sound power level, LWA, dB	124	126
Noise level, guaranteed sound power level, LWA, dB	128	130

5011

7013

Minimum working weight, kg (lb)	4750 (10470)	7000 (15430)
Impact rate, Long Stroke, bpm	370-530	350-450
Impact rate, Short Stroke, bpm	450-620	-
Operating pressure	160-170 (2320-2465)	150-170 (2175-2465)
Pressure relief, min bar (psi)	220 (3190)	220 (3190)
Pressure relief, max bar (psi)	230 (3335)	230 (3335)
Oil flow range, l/min (gal/min)	280-380 (74.0-100.4)	300-400 (79.3-105.7)
Back pressure, max bar (psi)	10 (145)	10 (145)
Input power, kW (hp)	108 (145)	113 (152)
Tool diameter, mm (in)	190 (7.48)	203 (7.99)
Carrier weight, allowed range, t (lb)	43-80 (94800-176400)	60-100 (132300-220500)
Noise level, measured sound power level, LWA, dB	122	125
Noise level, guaranteed sound power level, LWA, dB	126	129



ACCESSORIES

Rammer accessories for hydraulic hammers range from simple, practical auxiliary kits to advanced automatic Ramlube lubrication systems and effective AGW Unit. All the accessories will secure higher productivity, greater reliability and reduced owning and operating costs, with minimal environmental impact.



Ramlube I

Ramlube I can be used for lubricating the hammer tool and tool bushings. It can be fitted to all Rammer hammers with the pump unit housed within the carrier's engine compartment and is powered electrically. We recommend you to use only genuine Rammer tool grease for tool lubrication. Tool lubricant must have properties to withstand high temperature and extreme pressure, Rammer tool lubricants and automatic tool lubrication systems are especially designed to work with Rammer products.



Ramlube II

The Ramlube II greasing device can be installed to all Large Range hammers. Mounted on the hammer housing, the lubrication system features no external electric cables or hydraulic hoses for optimum wear and impact protection, Ramlube II contains a replaceable 500-gram grease cartridge. The greasing device is operated by the hydraulic pressure from the hammer's pressure fitting. Ramlube II is ideally suited to applications in which the hammer is required to work with more than one carrier.



Ramdata II

The Ramdata II service indicator is designed to help hammer operators and service personnel to get information about the service interval status, service history and accumulated working history of the hammer. Ramdata II is a standard feature to all Rammer Large range hammers.



AGW Unit

The AGW (Air, Grease and Water) Unit comprises the proven Ramair air flush system that prevents potentially harmful dust ingress, the Ramlube I automatic lubrication system to ensure consistent and throughout greasing, and Water jet dust suppression package which minimizes the creation of dust during breaking. Hydraulically actuated AGW Unit is especially designed to protect the hammer from the demands of extreme applications such as tunneling and heavy demolition and it keeps your Rammer hammer protected and productive throughout its working life.

FIRST CLASS SERVICE AND SUPPORT

Hammer installation

Installation inspection is an essential part of commissioning a new hammer, checking the compatibility of the hammer and carrier and ensuring that flows and pressures are adjusted correctly. Installation inspection together with correct operating methods guarantees reliable hammer operation.

Trained service personnel

Rammer products are renowned for quality, performance and reliability but when your hammer shows signs of natural wear, or the unexpected happens, our professional dealer service personnel are highly-trained, qualified and experienced which ensures that customers are never more than a phone call away from a Rammer hammer expert.

Genuine parts and tools

The Rammer global dealer network is the only place to access dedicated and experienced aftersales support. Genuine Rammer parts and tools availability is the best in class which keeps your hammer running at peak performance, ensuring downtime is reduced and enabling you to lower your operating and running costs.

We offer a wide range of tools designed for various applications and materials.



CHECKOUT
MORE FROM
OUR PARTS
AND TOOLS
BROCHURE.

Primary breaking

Standard chisel tool

- Non-abrasive but tough rock or concrete
- For material which has low or medium penetration rate



Hard rock chisel

- Hard and abrasive rock with fractures
- For applications where drilling and blasting cannot be used
- Materials with low penetration rate



Limestone and concrete chisel

- Very soft and easily breaking, non-abrasive rock or concrete
- For rock which has high penetration rate



Pyramid point tool

- Soft, non-abrasive and tough rock and especially concrete
- Materials requiring high penetration rate
- Where chisels have excessive retaining pin groove wear



Moil point tool

- Where chisels have excessive retaining pin groove wear
- Soft and nonabrasive rock
- General demolition of concrete



Secondary breaking and boom application

Blunt tool

- Hard rock with low or medium abrasive content
- Boulder breaking or concrete demolition
- Application where tool wear rate is low



Super blunt tool

- Hard and abrasive rock
- Only for boulder breaking
- 1.5...3 Times more wear life than standard blunt in very abrasive applications
- In non-abrasive applications life maybe shorter than standard blunt





GLOBAL DEALER NETWORK

Sandvik sells and supports its Rammer-branded products through a global dealer network that operates in 130 countries around the world.

YOUR LOCAL RAMMER DEALER



Rammer[®]

Sandvik Mining and Construction Oy
Taivalkatu 8, P.O.Box 165
FI-15101 Lahti, Finland
Phone Int. +358 205 44 151
www.rammer.com